

MSZ-HJ - INDOOR UNITS		MSZ-HJ25VA	MSZ-HJ35VA
CAPACITY (kW)	Heating (nominal)	3.15 (0.9-4.4)	3.6 (0.9-4.8)
	Cooling (nominal)	2.5 (0.9-3.0)	3.15 (1.0-3.7)
	Heating (UK)	2.61 (0.74-3.65)	2.99 (0.74-3.98)
	Cooling (UK)	2.48 (0.89-2.97)	3.12 (0.99-3.67)
SHF (nominal & UK)		0.89	0.87
COP / EER (nominal)		3.62 / 3.42	3.62 / 3.03
SCOP / SEER (BSEN14825)		3.8 / 5.1	3.8 / 5.1
ErP ENERGY EFFICIENCY CLASS Heating/Cooling		A / A	A / B
AIRFLOW (m ³ /min)	Heating/Cooling - Lo-Mi-Hi-SupHi	3.4-5.5-7.5-9.9 / 3.8-5.5-7.3-9.5	3.4-5.5-7.5-10.3 / 3.8-5.7-7.8-10.9
PIPE SIZE mm (in)	Gas	9.52 (3/8")	9.52 (3/8")
	Liquid	6.35 (1/4")	6.35 (1/4")
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling - Lo-Mi-Hi-SupHi	23-30-37-43 / 22-30-37-43	23-30-37-44 / 22-31-37-45
SOUND POWER LEVEL (dBA)		57	60
DIMENSIONS (mm)	Width x Depth x Height	799 x 232 x 290	799 x 232 x 290
WEIGHT (kg)		9	9
ELECTRICAL SUPPLY		220 - 240v, 50Hz	220 - 240v, 50Hz
FUSE RATING (BS88) - HRC (A)		10	10
INTERCONNECTING CABLE No. CORES		4	4

MUZ-HJ - OUTDOOR UNITS		MUZ-HJ25VA	MUZ-HJ35VA
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling	50 / 50	50 / 50
SOUND POWER LEVEL (dBA)	Cooling	63	64
WEIGHT (kg)		24	25
DIMENSIONS (mm)	Width x Depth x Height	699 x 249 x 530	699 x 249 x 530
ELECTRICAL SUPPLY		Fed by Indoor Unit	Fed by Indoor Unit
PHASE		Single	Single
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	0.870 / 0.730	0.995 / 1.040
	Heating/Cooling (UK)	0.79 / 0.58	0.90 / 0.83
STARTING CURRENT (A)		4.2	4.9
SYSTEM RUNNING CURRENT (A)	Heating/Cooling [MAX]	4.2 / 3.7 [5.8]	4.8 / 4.9 [6.5]
FUSE RATING (BS88) - HRC (A)		10	10
MAINS CABLE No. CORES		3	3
MAX PIPE LENGTH (m)		20	20
MAX HEIGHT DIFFERENCE (m)		12	12
CHARGE R410A (kg) - 7m		0.70	0.72